



Independent Bariatric  
Equipment Rental Specialists  
Tel 0800 193 2523  
info@fivemobility.co.uk  
www.fivemobility.co.uk

## Nitro Sante Bariatric HB 8000 Bed



The HB 8000 Sante Special Bariatric Bed is designed for use with plus sized patients in an acute care environment. The Sante Bariatric bed has a 125mm always engaged 5<sup>th</sup> wheel and is width adjustable to assist healthcare professionals when undertaking moving and handling tasks which in turn helps when the patient is required to be transported from ward to ward in the hospital. Width adjustment from 120cm (extended bed platform width) to 90cm (narrowed/standard bed platform width) ensures side rooms, hospital lifts and ward corridors are more accessible whilst patient remains in situ.

Rental Details;

Product Code: 5MSANTEACUTE	Other Features
SWL: 315KG - 50 Stone	Manual CPR
Width adjustable from 900mm to 1200mm	Electronic CPR
Castor Size: 150mm	Central Braking System
5 <sup>th</sup> Wheel Size: 125mm	CE Certified
Bed Height Min: 460mm	Soft Close Split Side Rail System
Bed Height Max: 860mm	Weigh Scale Option
Overall Bed Length: 2270mm	Attendant and Patient Control
Applications of Quality Management: ISO 9001:2015, ISO 14000:2015, EN 13485: 2014, EN 17025: 2015	



Independent Bariatric  
Equipment Rental Specialists  
Tel 0800 193 2523  
info@fivemobility.co.uk  
www.fivemobility.co.uk

Mattress Platform (narrowed)	900mm
Mattress Platform (extended)	1200mm
Bumper (outer edge)	1020mm
Surface Length	2000mm
Bumper to Bumper Length (outer edge)	2270mm
Side Rails outside to outside (narrowed)	985mm
Side Rails outside to outside (extended)	1285mm

### **Additional Features:**

#### **User Controls**

- Patient Handset.
- Attendant Handset with additional controls such as electronic CPR, Trendelenburg, Anti-Trendelenburg, one touch Cardiac Chair position.
- Attendant master lock out functions at patient handset.

#### **Side Rails**

- Split Side Rail system.
- Soft Close mechanism.
- Side Rails tested to 115kg loading.

#### **Castors**

- 150mm Castors per corner.
- 125mm central 5<sup>th</sup> wheel design.
- Central locking braking system.

#### **Safety Standards**

Standards and Regulations: EN 60601-2-52 2011, EN60601-1:2011, EN 60601-1:2009, EN ISO 14971:2013, 93/42/EEC, 90/384/EEC

Note: This Product is Also Available for Purchase