



Independent Bariatric
Equipment Rental Specialists
Tel 0800 193 2523
info@fivemobility.co.uk
www.fivemobility.co.uk

Minilift 160 Stand Aid



MiniLift160 is a mobile sit-to-stand lift which has been developed to, as gently as possible, assist the user when rising from a sitting to a standing position. When MiniLift160 is combined with the appropriate lifting accessories, the user gets support under the feet, for the front of the lower legs and behind the back, which provides for a safe and secure, yet active sit-to-stand procedure. To create optimal solutions for users with different needs, MiniLift160 can be used in combination with various accessories such as ThoraxSling, a specially adapted sit-to-stand vest, and CalfStrap. The bar of MiniLift160 can also be provided with a soft protection, SlingBarWrap MiniLift, which is sometimes needed for users with uncontrolled movements.

Product Code	5MMINILIFT160
SWL	160kg/25 stone
Accessories	Supplied with Disposable or Fabric Sling (rental)



Independent Bariatric
Equipment Rental Specialists
Tel 0800 193 2523
info@fivemobility.co.uk
www.fivemobility.co.uk

Accessories

ThoraxSling, polyester, XS-XXL, article no.: 45500003-009

ThoraxSling, wipeable, S-XXL, article no.: 45500004-009

ThoraxSling, with seat support, polyester, S-XL, article no.: 45600004-008

ThoraxSling, with seat support, disposable, non-woven, S-XL,
article no.: 45690004-008



TECHNICAL INFORMATION

Safe working load (SWL)	160 kg / 350 lbs
User length, min-max	1400-2000 mm / 55.1-78.7"
Material	Powder-coated steel
Height	980 mm / 38.6"
Length	919 mm / 36.2"
Length, folded	1098 mm / 43.2"
Width of base, outer measurement	669-959 mm / 26.3-37.8"
Width of base, inner measurement	531-773 mm / 20.9-30.4"
Weight	40.5 kg / 89.3 lbs
Base widening, EM	Manual
Base widening, EE	Electrical
Height of footplate, for user	59 mm / 2.3"
Castors, diameter, 60300010 and 60300012	100 mm / 3.9"
Rear castors, diameter, 60300011 and 60300013	100 mm / 3.9"
Front castors, diameter, 60300011 and 60300013	70 mm / 2.8"
Lifting speed, without load	35 mm / 1.4" per sec
Emergency lowering	Manual and electrical



All variants of MiniLift160 meet the requirements of the Medical Devices Directive for Class 1 products 93/42EEC.

Note: This Product is Also Available for Purchase